



Alternatori sincroni monofasi e trifasi a bassa tensione in corrente continua.
2 poli - 3000 giri/min.
Per le dimensioni vedere i modelli standard:
R80, EK, ET.

Synchronous single-phase and three-phase alternators low voltage, direct current.
2 poles - 3000 rpm.
For dimensions see standard models:
R80, EK, ET.



Caratteristiche tecniche / Technical characteristics

Tipo Type	Codice Code	Tensione Voltage Vdc V	Corrente Current Adc A	Potenza Power S1 kW	η %	Ripple %	Massa alternatore Alternator Mass kg
R 80 LBD	8367105CA406	12+12	25+25	0.6 (+1.5 AC)	73	48	13.8
EK 2 MAD	84401072.M	24	80	2.0	75	48	21.0
EK 2 MBD	84401095.M	24	125	3.0	77	48	24.0
EK 2 MCD	84401125.M	24	166	4.0	79	48	26.5
EK 2 LAD	84401150.M	24	200	4.8	82	48	31.0
EK 2 LCD	84401180.M	24	250	6.0	82	48	35.0
EK 2 MBD	84401095.M02	36	90	3.2	77	48	24.0
EK 2 MCD	84401125.M02	36	120	4.3	79	48	26.5
EK 2 LAD	84401150.M02	36	150	5.4	82	48	31.0
EK 2 LCD	84401180.M02	36	200	7.2	82	48	35.0
ET 2 MAD	81301072.M	24	100	2.4	74	5	25.5
ET 2 MBD	81301095.M	24	160	3.9	76	5	28.9
ET 2 MCD	81301125.M	24	200	4.8	79	5	32.8